

Seattle Kinetic Light



The Kinetic Light foot has a slightly higher build height than the standard Kinetic and includes a standard, easy-to-access male pyramid adapter. This foot also has a full-length, flexible keel.

Aimed at the moderate K2 activity user, this multi-axial foot can be set up with different ankle bumpers to suit the user's individual requirements, allowing for a soft heel strike, rapid progression to foot-flat and controlled progression to toe-off.

This makes it ideal for both transfemoral and transibial applications, as well as a weight range of 60kg to 160kg.

CES SEA F03: Use this code to read the Kinetic range clinical evaluation summary on the Steeper website.



***Water-resistant:** Safe for contact with water and occasional submersion. Rinse immediately with fresh water and dry following exposure to water, particularly salt or chlorinated.

Features and Benefits

- Multi-axial ankle within the foot shell
- Five exchangeable bumper options through the foot shell using the Kinetic tooling kit
- Excellent foot inversion/eversion and plantar flexion
- Full-length flexible keel
- Integral sandal toe cosmesis in two colour options
- Integral male pyramid
- 160kg weight limit

Cosmetics



Light/dark sandal toe footshell



Ordering Information

Trial Period - There is no trial period on this foot.

Impact Level Descriptions

Low: Low speed walking and low intensity activities - no variable cadence.

Low-Medium: Low impact activities and walking on uneven surfaces.

When ordering the Kinetic Light please use ordering example and category selection chart.

Part Number	Description	Available Sizes (cm)
NSKF100	9.5mm Heel, Light	22-30
NSKF103	9.5mm Heel, Dark	22-30

Ordering Example - NSKF100-25-L-4

Part Number	Size	Left/Right	Category
NSKF100	25	L	4

Spare Parts Ordering Information

Part Number	Description
NSKF-BMP-1	Soft Bumper
NSKF-BMP-2	Medium Bumper
NSKF-BMP-3	Firm Bumper
NSKF-BMP-4	Extra Firm Bumper
NSKF-BMP-5	XX Firm Bumper
NSKF-KIT	Maintenance Tool Kit - (Bumper installation tool)

Product Specification

Build Height and Heel Rise				Weight	
Part Number	Size (cm)	Build Height (cm)	Heel Rise (mm)	Cat 1-2	Cat 3-5
NSKF100	22-30	7.3	9.5	481g	564g
NSKF103	22-30	7.3	9.5	481g	564g

Feet - Trulife - Seattle Kinetic Light

Category Selection Chart:

Bumpers are coded according to Shore Durometer and based on foot size and patient weight. To optimise selection, follow the steps below to determine the appropriate category.

1. Locate the column associated with the amputee's foot size.
2. Locate the row corresponding to the amputee's weight.
3. The area where the column and row intersect lists the appropriate category.

Note: If the amputee has a long BK or carries heavy loads choose the next category higher.

	Foot Size									
Patient Weight	22	23	24	25	26	27	28	29	30	
137-160kg	-	-	-	-	5	5	5	5	5	
101-136kg	-	-	4	4	4	4	4	4	4	
81-100kg	-	2	3	3	3	3	3	3	-	
≤80 kg	1	1	2	2	2	2	2	-	-	

Weight Limit	Impact Level	Weight of Unit	Sizes (cm)	Build Height (cm)	Warranty
160kg		481g Size 25cm	22-30	7.3 Size 25cm	2 years Foot shell - 1 year