

Capital™ Knee



The Capital™ knee by College Park Industries is a yielding, hydraulic, single-axis knee joint that is easy to use for both patients and clinicians. This knee effortlessly accommodates the user's variable gait thanks to smooth and responsive hydraulics in both the swing and stance phases. The Capital knee is durable, sleek, and fresh water friendly, with easy mode selection and standard 4mm adjustments for quick setup/ installation. The Capital is a strong, reliable solution for moderate to high activity users.



***Waterproof note:** Following exposure to chlorinated water, rinse immediately with fresh water and dry.

Features and Benefits

- The Capital knee is designed to provide the user with a secure, responsive, and natural experience during the gait cycle
- The Capital Knee accommodates varying speeds from slow to fast using hydraulic control
- Due to its yielding mechanism, the Capital knee allows for controlled flexion of the knee during downhill walking, allowing for steady, smooth steps
- This lightweight, hydraulic knee can withstand many freshwater activities. Patients can wear the Capital in the shower as the moisture will not wear on the system
- The Capital's flexion, extension, and stance flexion resistance can all be adjusted using a 4mm hex wrench - so clinicians can dial in swing flexion and extension as well as stance flexion resistance without having to remove the device



Easy mode selection



Available in black, red, grey and white,

Knees - College Park - Capital™ Knee

Ordering Information

Trial Period - There is no trial period on this knee.

Impact Level Descriptions

Moderate: Daily activities include up to unlimited walking, climbing stairs and occasional moderate lifting (this does not include running).

Ordering Example - NCHKA-W-300			
Part ID	Colour	Distal Attachment	
NCHKA	-	-	
	Grey	Tube Clamp	300
	White	Pyramid Adapter	350
	Jet Black		
	Red		

Spare Parts Ordering Information

Additional Accessories	
Part Number	Description
NTA-S250-34	34mm Low Profile Tube Adapter, SS, 250mm
NTA-S430-34	34mm Low Profile Tube Adapter, SS, 430mm
Replacement Parts	
Part Number	Description
NCP-KP	Knee Pad Replacement Kit
NCP-KHB	Hydraulic Knee Bumper Replacement Kit
NTRP-J300	Trim Replacement Kit, Jet Black, 34mm Tube Clamp
NTRP-R300	Trim Replacement Kit, Red, 34mm Tube Clamp
NTRP-W300	Trim Replacement Kit, White, 34mm Tube Clamp
NTRP-G300	Trim Replacement Kit, Grey, 34mm Tube Clamp
NTRP-J350	Trim Replacement Kit, Jet Black, Pyramid Adapter
NTRP-R350	Trim Replacement Kit, Red, Pyramid Adapter
NTRP-W350	Trim Replacement Kit, White, Pyramid Adapter
NTRP-G350	Trim Replacement Kit, Grey, Pyramid Adapter
NCP-CRK	CPI Capital Cylinder Replacement Kit

Technical Information

Weight Limit	Impact Level	Weight	Total Flexion	Dome to Knee Centre	Build Height (cm)	Warranty
150kg	Moderate to High	980g (Pylon Receiver) 990g (Pyramid)	130°	17mm	23cm	3 Years

